

RAD-CAM PTZ RADIATION PROOF CAMERA



Model Number	GB-RAD-CAM-PTZ
Radiation Tolerance	Upto 1000 Rad
Ambient Temperature	-25° C - +60° C
Relative Humidity	Less than 95%(+25° C)
Enclosure protection	IP68
Support OSD Function	OSD Function
Support Long Focal Speed Limit Function	
Support 4 Alarm inputs, 2 Outputs	
128 Presets	
Horizontal 360 ° Unlimited rotation range Vertical +90° ~-90°	
Built-in surge and lightning protection devices	
Built-in heater and fan	

Image Sensor	1/4" CCD
Active Pixels	NTSC 768(H)x494(V),PAL 752(H)x582(V)
Synchronization	Internal
Video Output	VBS 1.0Vp-p/75 ohms
White Balance	Auto/Manual
Horizontal resolution	530TVL
S/N Ratio	50dB
Electronic Shutter	1/1~1/10, 000s
Min illumination	0.01Lux
Focal Length	f=34~1224mm
Focal & Lris	Auto/Manual
Pan Speed	0.1° ~80° /s
Tilt Speed	0.1° ~60° /s
Pan Range	360° Continuously
Tilt Range	+90° ~-90°
Preset	128(Max.)
Communication	Multi-protocol, RS485
Relative Humidity	90%
Work temperature	-30° C~55° C
Power consumption	60VA
Power supply	AC220V/AC24V

